



SPECIFICATIONS

Single sided / Dual sided Prints 300dpi Up to 16.7 million colours 256 Shades per pixel

Dve-sublimation/resin thermal transfer

up to 24 seconds per card / 150 cards per hour (YMC with transfer)*

- up to 29 seconds per card / 124 cards per hour (YMCK with transfer)*
- up to 40 seconds per card / 90 cards per hour (YMCKK with transfer)*

Input = 100 cards (.030"/.762 mm) Output = 200 cards (.030" / .762 mm) Prints Over-the-edge on CR-80 cards

Software Drivers

Windows 8/7/Vista (32bit & 64 bit) / Server 2008 & 2003/XP; Mac OS X v10.6 / v10.5 & Linux***



Software Features

Cardpresso XXS

Batch Printing Free Updates

DirectShow Image Acquisition WIA & TWAIN Image Acquisition Barcodes 1D Variable Objects Open Image from File Built in Image Editor Image Effects **Database Sources** Signature Acquisition Magnetic Encoding Printer Spooler Front Back Printing **Ethernet Printers Supprot** Overlay Panel Management



Ribbon Consumables

Fargo 84051 YMCK

500 Full Colour prints Use in conjunction with 84053 Ribbon

ID Photo Capture

PC Line 300K pixel Webcam

Features

Still Image capture Frame Rate 640 x 480 pixels @ 30fps Manual Focus **Snapshot Button**









