ID CARDS









PRINTER SPECIFICATIONS

Single sided Prints 300dpi Weight 9.7 lbs (4.4kg).

Colour dye sublimation, monochrome thermal printing and rewritable technology.

The user has the option to print a HoloKote® security watermark across the card surface. When used with HoloPatch® cards, one area of the HoloKote watermark is highlighted as a high visibility security seal. Magnetic stripe. Smart card encoding; Contact chip, MIFARE, DESFire and iClass.

2 years limited depot warranty.
USB rev1.1 (USB 2.0 compatible).
Windows 2000 Professional (SP4), XP, Vista & 7 (32/64 bit compatible), Server 2003 R2 SP2, 2008 (32/64 bit compatible).
270mm L x 215mm W x 233mm H (10.6"L x 8.4"W x 9.1"H).

35 seconds for colour and 7 seconds for monochrome.



Software Features

Cardpresso XXS

DirectShow Image Acquisition WIA & TWAIN Image Acquisition Barcodes 1D Variable Objects Open Image from File Built in Image Editor Image Effects **Database Sources** Signature Acquisition Magnetic Encoding Printer Spooler Front Back Printing **Ethernet Printers Supprot** Overlay Panel Management Batch Printing Free Updates



Ribbon Consumables

MA100YMCKO

100 Full Colour prints

ID Photo Capture

PC Line 300K pixel Webcam Features

Still Image capture Frame Rate 640 x 480 pixels @ 30fps Manual Focus Snapshot Button







