

# Dualys<sup>3</sup>

The dual-sided color printer for plastic card personalization



Color &  
Monochrome  
Thermal  
Transfer



300 dpi



Dual-sided



29 s/card



0.25 - 1 mm  
(10 - 40 mil)



3 years

**evolis**

[www.evolis.com](http://www.evolis.com)

From bulk personalization of cards to individual card printing, **Dualys<sup>3</sup>** is the one-stop color printer for dual-sided personalization of badges, sterling quality and robust security.

Thanks to the most advanced printing engine in the market, **Dualys<sup>3</sup>** prints high-definition badges within seconds. This solution benefits from the latest encoding technologies: ISO or JIS2 magnetic tracks, and smart card with contact or contactless (RFID). These encoding options can be combined to personalize multifaceted cards in a single pass, paving the way to a wide range of market applications in various industries: identification, biometric security, transport, financial institutions, educational organizations, loyalty programs, and leisure.

**Dualys<sup>3</sup>** comes with a detachable 100-card feeder. Yet, you can also use it as a compact counter, thanks to a manual feed option that prints your badges one by one.

Because the Evolis products have earned market-proven reliability, Evolis is committed even further to superior quality and introduces a **3-year warranty** on the full **Dualys<sup>3</sup>** range of printers.

## GENERAL SPECIFICATIONS

- Color printing module
- 300 dpi print head (11.8 dots/mm)
- USB connection. Option for Ethernet TCP-IP connection
- 16 MB RAM allowing storage of two cards (front & back)
- Flip-over station for dual-sided printing
- Detachable feeder with a capacity of 100 cards (0.76 mm - 30 mil)
- Output hopper with a capacity of 100 cards (0.76 mm - 30 mil)
- 1-Button and 4-LED control panel

## PRINT MODES

- Color dye sublimation and monochrome thermal transfer
- Enhanced color management system
- Edge-to-edge printing
- Dual-sided printing
- Integrated ribbon saver for monochrome printing

## PRINTING SPEED

Personalization throughput will depend on card design and printer settings.

- Color 1 side (YMCKO): 150 cards/hour
- Color 2 sides (YMCKO-K): 125 cards/hour
- Monochrome 1 side: up to 1000 cards/hour<sup>1</sup>
- Monochrome 2 sides: up to 350 cards/hour<sup>1</sup>

## SUPPORTED PLATFORMS

- Windows™ XP, Server 2003 and Vista 32 & 64 bits
- Mac™ OS X v10.2, 10.3 and 10.4
- Linux

## SUPPLIED SOFTWARE

- eMedia Card Designer Software for designing and editing badges
- Compatible with Windows™ XP, Server 2003 and Vista 32 & 64 bits
- Connection to Microsoft™ Excel databases

## RIBBON TYPES

- 2-panel KO black monochrome ribbon - 500 cards/roll
- 5-panel YMCKO color ribbon - 200 cards/roll
- 6-panel YMCKO-K color ribbon - 200 cards/roll
- Half-panel YMCKO color ribbon - 400 cards/roll
- Monochrome ribbons - up to 1000 cards/roll (black, red, green, blue, white, gold and silver)
- Special ribbons:
  - Varnish hologram - 350 cards/roll
  - Scratch-Off - up to 1000 cards/roll
  - BlackWAX monochrome ribbon (for ABS & special varnished plastic cards) - up to 1000 cards/roll


## OPTIONS

- Encoding options (can be combined):
  - Magnetic stripe encoder ISO 7811 HiCo/LoCo or JIS2
  - Smart contact station - ISO 7816-2
  - Smart contact station and encoding unit - PC/SC, EMV 2000-1
  - Contactless encoding unit - ISO 14443A, B, ISO 15693, Mifare, DesFire, HID iCLASS
  - Other types upon request
- 100-card additional feeder
- Manual card feeder
- Travel bag
- Cleaning kits

## WARRANTY

Use Evolis Genuine products for best performance and extended lifespan of your printer.

- Printer, print head: 3-year warranty, unlimited number of passes<sup>2</sup>



### Card types

### Card format

### Card thickness

### Card feeder capacity

### Card output hopper capacity

### Printer size

### Printer weight

### Connections

### Electrical

### Environmental

- All PVC, Composite PVC cards, PET, ABS<sup>1</sup> and special varnished<sup>1</sup> cards
- ISO CR-80 - ISO 7810 (53.98 mm x 85.60 mm - 3.375" x 2.125")
- From 0.25 mm (10 mil) to 1 mm (40 mil) - Dual-sided printing recommended from 0.50 mm (20 mil)
- 100 cards (0.76 mm - 30 mil), 300 cards (0.25 mm - 10 mil)
- 100 cards (0.76 mm - 30 mil), 300 cards (0.25 mm - 10 mil)
- Height: 235 mm (9.25") - Length: 447 mm (17.59") - Width: 237 mm (9.33")
- 7.4 Kg (16.31 Lbs)
- USB (cable supplied) - Option for Ethernet TCP-IP
- Power supply: 100-240 V AC, 50-60 Hz, 1.8 A - Printer: 24 V DC, 3 A
- Min/max operating temperature: 15° / 30° C (59° / 86° F)  
Humidity: 20% to 65% non-condensing
- Min/max storage temperature: -5° / +70° C (23° / 158° F)  
Storage humidity: 20% to 70% non-condensing
- Operating ventilation: free air

1. Under specific conditions.

2. Subject to observance of specific conditions and use of Evolis genuine consumables.



**evolis**

### EUROPE, MIDDLE EAST, AFRICA

#### Evolis Card Printer

14, avenue de la Fontaine  
Z.I. Angers Beaucozéz  
49070 Beaucozéz - France  
Tel: + 33 (0) 241 367 606  
Fax: + 33 (0) 241 367 612  
info@evolis.com

### AMERICAS

#### Evolis Inc.

1835 South Perimeter Road  
Suite 190 - Fort Lauderdale  
FL 33309 - USA  
Tel: (954) 491-9898  
Fax: (954) 491-5140  
evolisinc@evolis.com

### ASIA PACIFIC

#### Evolis Asia Pte Ltd

120 Lower Delta Road  
#13-12 Cendex Centre  
Singapore 169208  
Tel: +65 6377 9731  
Fax: +65 6278 7002  
evolisasia@evolis.com

**IDMANAGEMENT**  
SYSTEMS

www.idmanagement.com  
ID Management Systems  
Temple Court, Cathedral Road  
Cardiff  
CF11 9HA  
United Kingdom  
Tel: +44 (0) 2920 786 419  
Fax: 08707413001  
E-mail: sales@idmanagement.com  
Web: www.idmanagement.com