

# Desktop Card Printer

From NBS Technologies

## Javelin® J230i

The J230i is our entry level card printer with built-in input hopper and output stacker. It prints in colour or monochrome, and an optional flipper is available for dual-side printing. The Javelin J230i card printer is reliable, compact and easy-to-use, delivering outstanding performance at a great price.

USB and Ethernet connectivity are standard features and a full range of encoding options are available. A colour ribbon and Javelin Card Designer ID card application software are supplied with each printer.



## START PRINTING OUT OF THE BOX!

### In the Box

- YMCKO Roll
- USB Cable
- Cleaning Kit (Cards)
- Javelin Designer™ Create Software



## THE JAVELIN® J230i OFFERS THESE KEY FEATURES AND BENEFITS:



### COMPACT AND FLEXIBLE

- Small footprint easily fits into a wide range of locations
- Conveniently fits on the desktop or under the counter
- Prints in full colour or monochrome
- Flipper for dual-side printing (option)



### NETWORK AND ENCODING

- 3-track magnetic stripe encoding (HiCo/LoCo) (option)
- Contact and contactless smart card encoding capabilities (option)
- Built-in 10/100 Ethernet for printer networking
- Internal USB hub to connect camera, memory stick and other peripheral devices



### EASY-TO-USE

- User-friendly USB plug-and-play set-up
- LCD screen displays printer status and diagnostics
- Easy to change ribbon and thermal print head
- RFID colour ribbon protection
- 100-card input hopper
- ID card software included with each printer

CONSULTING

SOFTWARE

HARDWARE

SMART CARD EQUIPMENT



Total  
Card Solutions

IDMANAGEMENT  
www.idmanagement.com SYSTEMS

ID Management Systems  
Temple Court, Cathedral Road  
Cardiff  
CF11 9HA  
United Kingdom  
Tel : +44 (0) 2920 786 410  
Fax : 08707413001  
E-mail : sales@idmanagement.com  
Web : www.idmanagement.com

WWW.NBSTECH.COM

## Printer Specifications

<b>Print Mode</b>	Single-side printing (option: dual-side printing)	
<b>Print Method</b>	Thermal transfer (mono), Dye-sublimation (colour)	
<b>Print speed</b>	Mono: 550 cph, YMCKO: 170 cph (single-side) YMCKOK: 140 cph (dual-side)	
<b>Ribbons</b>	KrO: 500 prints/roll, YMCKO: 200 prints/roll, YMCKOK: 167 prints/roll, Half-panel YMC plus full-panel KO: 300 prints/roll Monochrome: black, silver, gold, red, blue, white, scratch-off: 1000 prints/roll	
<b>Card encoding options</b>	Magnetic Stripe: ISO7811 (tracks 1, 2, 3); Hi-Co/Lo-Co, Head life - 4,000,000 passes Contact (IC): ISO 7816, EMV, PC/SC, IC contact life: 1,000,000 passes Contactless (RF): MiFare, ISO 14443 A,B, ISO15693	
<b>Warranty</b>	30 months printer and print head (unlimited passes)	
<b>Printer interfaces</b>	USB 2.0; internal USB hub to connect peripheral devices; built-in Ethernet (10/100Mbps) RS232 network	
<b>Software drivers</b>	Windows 2000, XP, Server 2003/2008, Vista, Windows 7	
<b>Fonts/Images</b>	300 dots per inch (11.8 dots per mm) resolution, 16.7 million colours True Type fonts via Windows drivers	
<b>Barcodes</b>	Code 39, Code 128 B & C with & without check digit, 2 of 5 interleaved, UPC-A, EAN 8 & EAN 13 PDF-417 2D barcode and other symbols can be printed via Windows® drivers	
<b>Card capacity</b>	Input hopper: 100 cards; Output stacker: 70 cards Single card feeding also available	
<b>Dimensions</b>	Single-side: 403mm (L) x 202mm (H) x 192mm (W) 15.8" x 8.0" x 7.6"	Dual-side: 471mm (L) x 202mm (H) x 192mm (W) 18.5" x 8.0" x 7.6"
<b>Weight</b>	Single-side: 5.5 kg / 12.1 lbs	Dual-side: 6.0 kg / 13.2 lbs
<b>Power source</b>	Input: 100V - 250V, 50/60Hz; Output: DC 24V (FCC Class B, CE and UL & CUL approved)	
<b>CPU &amp; RAM</b>	CPU: 32 bit processor RAM: 16MB	
<b>Environment</b>	Operating temperature: 0 - 50°C / 32 - 122°F, 20 - 90% RH Storage temperature: -25 - 70°C / -13 - 158°F	
<b>Built-in Security</b>	Kensington® ClickSafe™ security anchor; locking input hopper (option)	

## Card Specifications

<b>Types</b>	PVC & composite PVC
<b>Card width/length</b>	ISO CR-80-ISO 7810: 53.98mm (W) x 85.60mm (L) / 3.375" x 2.125"
<b>Card thickness</b>	0.5mm - 1.2mm; 20mil - 50mil



Ships with everything you need to start printing



Optional Card Flipper



Easy to read LCD screen



Input hopper & Output stacker



w: www.nbstech.com  
e: javelin@nbstech.com

Corporate Headquarters  
Canada  
703 Evans Avenue  
Toronto, Ontario  
M9C 5E9  
Canada  
tel: +1 416.621.1911  
fax: +1 416.621.8875

Contact our NBS card personalization experts for full details on this and other card personalization products at:

Europe, Middle East, Africa  
B1 Moorfield Point  
Slyfield Industrial Park  
Guildford, Surrey GU1 1RU  
United Kingdom  
tel: +44 (0)1483 563200  
fax: +44 (0)1483 511189

North / South America  
10925 Bren Road E  
Minneapolis, MN 55343  
USA  
tel: +1 416.840.8620  
fax: +1 952.912.9439

Asia Pacific  
PO Box 780  
Hurstville BC  
NSW 1481  
Australia  
tel: +61 (2) 9546 6841  
fax: +61 (2) 9546 6851